



[Knowledgebase](#) > [Power Management](#) > [external I/O](#) > [What are the differences between IKD1M and new IKD-IN-16 & IKD-OUT-16](#)

What are the differences between IKD1M and new IKD-IN-16 & IKD-OUT-16

Justin Schneider - 2026-07-27 - [external I/O](#)

	IKD1M 	IKD-IN-16 	IKD-OUT-16
Housing dimensions (L x W x H mm)	168 x 128 x 51	108 x 90 x 61	162 x 90 x 61
I/O	8x discrete inputs 8x configurable 3-pole relays outputs (Form C)	16x discrete inputs	12 x configurable 2-pole relay outputs (Form A) 4 x configurable 3-pole relay outputs (Form C)
Power supply	12/24 VDC (6 to 36 VDC)	12/24 VDC (9 to 35 VDC)	24 VDC (19 to 35 VDC)
Annunciation	8x DI status LED	1x power LED 1x CAN LED 16x DI status LED	1x power LED 1x CAN LED

Configuration

PC tool and
DPC cable

DIP switches for CAN
address (1/2) and
CAN speed (500/250 kbps)
*No software programming
required.*

[Downloads](#)

[Downloads](#)

[Downloads](#)

Note:

The new IKD modules have been designed to seamlessly communicate with easYgen devices without requiring a software update for the easYgens. This ensures that any easYgen or power management product previously supporting IKD modules will automatically support the new IKDs by default.

Please note that there may be exceptions with certain legacy products, such as GCP, where compatibility could vary.

A PDF article concerning the first (non-UL certified) generation IKD-IN-16 and IKD-OUT-16 is attached.