



[Knowledgebase](#) > [Hydraulic Governor/Actuator](#) > [Oils for Hydraulic Governors/Actuators \(Ref. 25071\)](#)

Oils for Hydraulic Governors/Actuators (Ref. 25071)

John - 2024-09-27 - [Hydraulic Governor/Actuator](#)

Woodward reserves the right to update any portion of this publication at any time. Information provided herein by Woodward is believed to be correct and reliable. However, Woodward assumes no responsibility for the information and/or its use, unless otherwise expressly undertaken. Further, with respect to the information and/or its use, Woodward disclaims all warranties, express or implied, including any warranty against infringement, of title, merchantability or fitness for a particular purpose, or arising from trade or custom.

This article serves as a general guide for anyone involved in the selection of oils for use in Woodward governors or actuators.

One of the primary functions required of an oil is to stand up to high loadings and high temperatures, while remaining a good lubricant. Oil, as it emerges from the refinery process, is a slippery liquid, but it lacks additives vital to its intended functions.

These additives turn a liquid into a lubricant that fights heat, cold, contamination, corrosion, rust, wear, and other environmental and mechanical hazards. Lubricant additives are grouped into three general categories according to the functions they perform:

- protect the lubricated surface
- improve lubricant performance
- protect the lubricant

Surface protective additives include anti-wear agents, corrosion and rust inhibitors, and detergents and dispersants. Performance additives include pour point depressants, seal swell agents, and viscosity index improvers. Lubricant protective additives cover anti-foamants, anti-oxidants, and metal deactivators.

See detailed information in the attached document.

- Tags
- [Hydraulic](#)
- [Oil](#)

Attachments

- [B25071 - OILS FOR HYDRAULIC CONTROLS.pdf \(340.73 KB\)](#)